

Model #: 850

UPC: 649532008506

MSRP: \$23.99



The CyberPower 850 surge suppressor is a Home/Office Computer Surge Protector and is fully internet-ready with 1-in / 2-out phone/fax/modem protection. This model is ideal for personal computers, phones/fax/modems, printers, stereos, and CD/DVD players. 2400 joule MOV technology safely guards the surge suppressor and connected electronics against line abnormalities and lightning surges. EMI/RFI filtering blocks unwanted line noise from all connected electronics. CyberPower fully stands behind its products with a lifetime product warranty and Connected Equipment Guarantee of \$75,000.

- MOV (Metal Oxide Varistor) MOV technology allows normal current to pass through the device, while diverting any surge/spikes through the ground circuit. This safely protects all connected electronics along with the surge suppressor itself.
- Built-In Automatic Shutdown In the event that the surge/spike exceeds the unit's ability to suppress the signal, the CyberPower surge suppressor will safely shut itself down to protect all connected electronics.
- Transformer-spaced Outlets Widely spaced outlets allow you to conveniently add large transformer-based plugs without compromising the utility of other outlets.
- EMI/RFI Shielding Provides shielding against electromagnetic interference & radio frequency signals. Most commonly, this is used to prevent line noise or "humming" that occurs over telephone lines or stereo electronics.
- ISO & Safety Certifications All CyberPower's manufacturing facilities are ISO-9001 Quality Tested. Our products are also UL Listed and CSA Certified.
- Child-safe Outlets: Outlets on the surge suppressor that are not used can be "closed off" so unwanted objects cannot be electrically charged.
- Keyhole Mounting Slots Convenient mounting slots are located on the back on the surge suppressor.
- Sturdy ABS Case Constructed of impact-resistant composite material for maximum durability.

Technical Specifications

General	
Model #	850
Wodel #	630
Input	
Voltage	110/120V Nominal
Plug Type	NEMA 5-15P
Plug Style	Right-angle
Cord Length	6 ft
<u> </u>	
Output	
Outlets - Total	8
Outlets - Widely Spaced	4 x NEMA 5-15R
Outlets - Normal Spaced	4 x NEMA 5-15R
Surge Protection and Filtering	
Surge Suppression	2400 Joules
Phone Protection (RJ11)	One-in/Two-out
Ethernet Protection (RJ45)	None
Coax Protection (RG6)	None
Maximum Surge Current	120,000 Amps
Maximum Surge Current H-N	90,000 Amps
Maximum Surge Current H-G	15,000 Amps
Maximum Surge Current N-G	15,000 Amps
Maximum Surge Voltage	6,000V
Clamping Voltage	330 V
Response Time	<1 ns
EMI/RFI Filtration	EMI/RFI 150KHz to 100MHz
Attenuation	Up to 58dB
Indicators	
Indicator Lights	Power (Red); Surge (Red); Ground (Green)
Physical	40.75" 4" 4.5"
Dimensions (WxHxD)	10.75" x 4" x 1.5"
Weight	1.7875 lbs.
Color	Black
Warranty	
Product Warranty	Lifetime
Connected Equipment Guarantee	Lifetime
CEG Amount	\$75,000
020 / milourit	ψ. 0,000